
better-boto

Release 0.5.20

eamonn faherty

Nov 07, 2019

CONTENTS:

1 Client	3
1.1 What is this?	3
1.2 Classes	3
2 CloudFormation helpers	5
2.1 What is this?	5
2.2 Methods	5
3 CodeBuild helpers	7
3.1 What is this?	7
3.2 Methods	7
4 CodeCommit helpers	9
4.1 What is this?	9
4.2 Methods	9
5 GuardDuty helpers	11
5.1 What is this?	11
5.2 Methods	11
6 Cloudwatch logs helpers	13
6.1 What is this?	13
6.2 Methods	13
7 Organizations helpers	15
7.1 What is this?	15
7.2 Methods	15
8 Service Catalog helpers	17
8.1 What is this?	17
8.2 Methods	17
Python Module Index	19
Index	21

Better Boto aims to reduce the burden of using AWS Boto3. AWS Boto3 is a low level SDK for interacting with AWS Services and sometimes it feels too low level or too crud like.

Better Boto is a collection of helper functions to make using AWS Boto easier. For example, it added a `create_or_update` method to the AWS CloudFormation client. It also provides some helpers for dealing with pagination operations and some help using AWS Organizations. Check out the API for more info.

CHAPTER ONE

CLIENT

1.1 What is this?

With the following clients you can use them as context managers and they provide extra functionality for you. Each client is documented below:

1.2 Classes

```
class betterboto.client.ClientContextManager(service_name, **kwargs)
```

ClientContextManager allows you to use boto3 client as a python context manager. This allows you to perform the following:

```
with ClientContextManager('cloudformation') as cloudformation_client:  
    cloudformation_client.create_stack(**args)
```

```
class betterboto.client.CrossAccountClientContextManager(service_name, role_arn,  
                                                       role_session_name,  
                                                       **kwargs)
```

CrossAccountClientContextManager allows you to use boto3 client as a python context manager for another account. This allows you to perform the following:

```
with CrossAccountClientContextManager(  
    'cloudformation',  
    'arn:aws:iam::0123456789010:role/deployer',  
    'deployment_account_session',  
) as deployment_account_cloudformation:  
    deployment_account_cloudformation.create_stack(**args)
```

```
class betterboto.client.CrossMultipleAccountsClientContextManager(service_name,  
                                                               assum-  
                                                               able_details,  
                                                               **kwargs)
```

CrossMultipleAccountsClientContextManager allows you to use boto3 client as a python context manager for another account. This allows you to perform the following:

```
with CrossMultipleAccountsClientContextManager(  
    'cloudformation',  
    [  
        ('arn:aws:iam::0123456789010:role/deployer', 'deployment_account_session  
        ↵'),  
        ('arn:aws:iam::097167856333:role/deployer', 'deployment_account_session_  
        ↵nested'),  
    ])
```

(continues on next page)

(continued from previous page)

```
    ],
) as deployment_account_cLOUDformation:
    deployment_account_cLOUDformation.create_stack(**args)
```

```
class betterboto.client.MultiRegionClientContextManager(service_name, regions,
                                                       **kwargs)
```

MultiRegionClientContextManager allows you to use boto3 client as a python context manager for multiple regions. This allows you to perform the following:

```
with MultiRegionClientContextManager('cloudformation', ['us-east-1', 'eu-west-1']) as cloudformation_clients:
    for region_name, cloudformation_client in cloudformation_clients.items():
        cloudformation_client.create_stack(**args)
```

If you want to deploy to multiple regions at the same time then you should use Python Threads

CLOUDFORMATION HELPERS

2.1 What is this?

The following methods are added to clients instantiated using Betterboto:

2.2 Methods

betterboto.cloudformation.**create_or_update**(*self*, ***kwargs*)

For the given template and stack name, this method will create a stack if it doesn't already exist otherwise it will generate a changeset and then execute it. This method will wait for the operation to complete before returning and in the instance of an error it will print out the stack events to help you debug more easily.

Parameters

- **self** – cloudformation client
- **kwargs** – these are passed onto the create_stack and create_change_set method calls

Returns

None

betterboto.cloudformation.**describe_stacks_single_page**(*self*, ***kwargs*)

This will continue to call describe_stacks until there are no more pages left to retrieve. It will return the aggregated response in the same structure as describe_stacks does.

Parameters

- **self** – servicecatalog client
- **kwargs** – these are passed onto the describe_stacks method call

Returns

servicecatalog_client.describe_stacks.response

betterboto.cloudformation.**ensure_deleted**(*self*, *StackName*)

This will check if there is a stack with the given StackName in a state that can be deleted. If there is, it will delete it.

Parameters

- **self** – cloudformation client
- **StackName** – This is the name of the stack that should be deleted

Returns

None

CODEBUILD HELPERS

3.1 What is this?

The following methods are added to clients instantiated using Betterboto:

3.2 Methods

`betterboto.codebuild.start_build_and_wait_for_completion(self, **kwargs)`

This will start a build of an AWS CodeBuild Project and wait for it to complete. It will return the result of the build.

Parameters

- **self** – codebuild client
- **kwargs** – these are passed onto the start_build method call

Returns `codebuild_client.batch_get_builds.response[0]`

CODECOMMIT HELPERS

4.1 What is this?

The following methods are added to clients instantiated using Betterboto:

4.2 Methods

betterboto.codecommit.**list_branches_single_page**(*self*, ***kwargs*)

This will continue to call list_branches until there are no more pages left to retrieve. It will return the aggregated response in the same structure as list_branches does.

Parameters

- **self** – codecommit client
- **kwargs** – these are passed onto the list_branches method call

Returns codecommit_client.list_branches.response

GUARDDUTY HELPERS

5.1 What is this?

The following methods are added to clients instantiated using Betterboto:

5.2 Methods

`betterboto.guardduty.list_members_single_page(self, **kwargs)`

This will continue to call `list_members` until there are no more pages left to retrieve. It will return the aggregated response in the same structure as `list_members` does.

Parameters

- **self** – guardduty client
- **kwargs** – these are passed onto the `list_members` method call

Returns `guardduty_client.list_members.response`

CLOUDWATCH LOGS HELPERS

6.1 What is this?

The following methods are added to clients instantiated using Betterboto:

6.2 Methods

`betterboto.logs.get_log_events_single_page(self, **kwargs)`

This will continue to call `get_log_events` until there are no more pages left to retrieve. It will return the aggregated response in the same structure as `get_log_events` does.

Parameters

- **self** – logs client
- **kwargs** – these are passed onto the `get_log_events` method call

Returns `logs.get_log_events.response`

ORGANIZATIONS HELPERS

7.1 What is this?

The following methods are added to clients instantiated using Betterboto:

7.2 Methods

betterboto.organizations.**convert_path_to_ou**(*self, path*)

This method accepts a path and returns the ou. This raises an exception when converting / and you have more than one root

Parameters

- **self** – organizations client
- **path** – organizations path

Returns the ou of the path specified

betterboto.organizations.**list_accounts_single_page**(*self, **kwargs*)

This will continue to call list_accounts until there are no more pages left to retrieve. It will return the aggregated response in the same structure as list_accounts does.

Parameters

- **self** – organizations client
- **kwargs** – these are passed onto the list_accounts method call

Returns organizations_client.list_accounts.response

betterboto.organizations.**list_children_nested**(*self, **kwargs*)

This method will return a list of all children (either ACCOUNT or ORGANIZATIONAL_UNIT) for the given ParentId. It includes children, grandchildren lower levels of nesting.

Parameters

- **self** – organizations client
- **kwargs** – these are passed onto the list_children method call

Returns list of children in the structure of [{‘Id’: “0123456789010”}, {‘Id’: “1009876543210”}]

betterboto.organizations.**list_children_single_page**(*self, **kwargs*)

This will continue to call list_children until there are no more pages left to retrieve. It will return the aggregated response in the same structure as list_children does.

Parameters

- **self** – organizations client
 - **kwargs** – these are passed onto the list_children method call

Returns organizations_client.list_children.response

betterboto.organizations.list_organizational_units_for_parent_single_page(self, **kwargs)

This will continue to call `list_organizational_units_for_parent` until there are no more pages left to retrieve. It will return the aggregated response in the same structure as `list_organizational_units_for_parent` does.

Parameters

- **self** – organizations client
 - **kwargs** – these are passed onto the list_organizational_units_for_parent method call

Returns organizations_client.list_organizational_units_for_parent.response

```
betterboto.organizations.search_products_as_admin_single_page(self, **kwargs)
```

This will continue to call `search_products_as_admin` until there are no more pages left to retrieve. It will return the aggregated response in the same structure as `search_products_as_admin` does.

Parameters

- **self** – organizations client
 - **kwargs** – these are passed onto the search_products_as_admin method call

Returns organizations_client.search_products_as_admin.response

SERVICE CATALOG HELPERS

8.1 What is this?

The following methods are added to clients instantiated using Betterboto:

8.2 Methods

```
betterboto.servicecatalog.list_accepted_portfolio_shares_single_page(self,  
                           **kwargs)
```

This will continue to call list_accepted_portfolio_shares until there are no more pages left to retrieve. It will return the aggregated response in the same structure as list_accepted_portfolio_shares does.

Parameters

- **self** – servicecatalog client
- **kwargs** – these are passed onto the list_accepted_portfolio_shares method call

Returns servicecatalog_client.list_accepted_portfolio_shares.response

```
betterboto.servicecatalog.list_launch_paths_single_page(self, **kwargs)
```

This will continue to call list_launch_paths until there are no more pages left to retrieve. It will return the aggregated response in the same structure as list_launch_paths does.

Parameters

- **self** – servicecatalog client
- **kwargs** – these are passed onto the list_launch_paths method call

Returns servicecatalog_client.list_launch_paths.response

```
betterboto.servicecatalog.list_portfolios_for_product_single_page(self,  
                     **kwargs)
```

This will continue to call list_portfolios_for_product until there are no more pages left to retrieve. It will return the aggregated response in the same structure as list_portfolios_for_product does.

Parameters

- **self** – servicecatalog client
- **kwargs** – these are passed onto the list_portfolios_for_product method call

Returns servicecatalog_client.list_portfolios_for_product.response

```
betterboto.servicecatalog.list_portfolios_single_page(self, **kwargs)
```

This will continue to call `list_portfolios` until there are no more pages left to retrieve. It will return the aggregated response in the same structure as `list_portfolios` does.

Parameters

- **self** – servicecatalog client
 - **kwargs** – these are passed onto the list_portfolios method call

Returns servicecatalog_client.list_portfolios.response

```
betterboto.servicecatalog.list_provisioned_product_plans_single_page(self,  
**kwargs)
```

This will continue to call `list_provisioned_product_plans` until there are no more pages left to retrieve. It will return the aggregated response in the same structure as `list_provisioned_product_plans` does.

Parameters

- **self** – servicecatalog client
 - **kwargs** – these are passed onto the list_provisioned_product_plans method call

Returns servicecatalog_client.list_provisioned_product_plans.response

```
betterboto.servicecatalog.list_provisioning_artifacts_single_page(self,  
    **kwargs)
```

This will continue to call `list_provisioning_artifacts` until there are no more pages left to retrieve. It will return the aggregated response in the same structure as `list_provisioning_artifacts` does.

Parameters

- **self** – servicecatalog client
 - **kwargs** – these are passed onto the list_provisioning_artifacts method call

Returns servicecatalog_client.list_provisioning_artifacts.response

```
betterboto.servicecatalog.search_products_as_admin_single_page(self, **kwargs)
```

This will continue to call `search_products_as_admin` until there are no more pages left to retrieve. It will return the aggregated response in the same structure as `search_products_as_admin` does.

Parameters

- **self** – servicecatalog client
 - **kwargs** – these are passed onto the search_products_as_admin method call

Returns servicecatalog_client.search_products_as_admin.response

```
betterboto.servicecatalog.search_provisioned_products_single_page(self,  
    **kwargs)
```

This will continue to call `search_provisioned_products` until there are no more pages left to retrieve. It will return the aggregated response in the same structure as `search_provisioned_products` does.

Parameters

- **self** – servicecatalog client
 - **kargs** – these are passed onto the search_provisioned_products method call

Returns servicecatalog client.search provisioned products.response

PYTHON MODULE INDEX

b

`betterboto.client`, 3
`betterboto.cloudformation`, 5
`betterboto.codebuild`, 7
`betterboto.codeccommit`, 9
`betterboto.guardduty`, 11
`betterboto.logs`, 13
`betterboto.organizations`, 15
`betterboto.servicecatalog`, 17

INDEX

B

betterboto.client (*module*), 3
betterboto.cloudformation (*module*), 5
betterboto.codebuild (*module*), 7
betterboto.codecommit (*module*), 9
betterboto.guardduty (*module*), 11
betterboto.logs (*module*), 13
betterboto.organizations (*module*), 15
betterboto.servicecatalog (*module*), 17

C

ClientContextManager (*class in betterboto.client*), 3
convert_path_to_ou () (*in module betterboto.organizations*), 15
create_or_update () (*in module betterboto.cloudformation*), 5
CrossAccountClientContextManager (*class in betterboto.client*), 3
CrossMultipleAccountsClientContextManager (*class in betterboto.client*), 3

D

describe_stacks_single_page () (*in module betterboto.cloudformation*), 5

E

ensure_deleted () (*in module betterboto.cloudformation*), 5

G

get_log_events_single_page () (*in module betterboto.logs*), 13

L

list_accepted_portfolio_shares_single_page () (*in module betterboto.servicecatalog*), 17
list_accounts_single_page () (*in module betterboto.organizations*), 15
list_branches_single_page () (*in module betterboto.codecommit*), 9

list_children_nested () (*in module betterboto.organizations*), 15
list_children_single_page () (*in module betterboto.organizations*), 15
list_launch_paths_single_page () (*in module betterboto.servicecatalog*), 17
list_members_single_page () (*in module betterboto.guardduty*), 11
list_organizational_units_for_parent_single_page () (*in module betterboto.organizations*), 16
list_portfolios_for_product_single_page () (*in module betterboto.servicecatalog*), 17
list_portfolios_single_page () (*in module betterboto.servicecatalog*), 17
list_provisioned_product_plans_single_page () (*in module betterboto.servicecatalog*), 18
list_provisioning_artifacts_single_page () (*in module betterboto.servicecatalog*), 18

M

MultiRegionClientContextManager (*class in betterboto.client*), 4

S

search_products_as_admin_single_page () (*in module betterboto.organizations*), 16
search_products_as_admin_single_page () (*in module betterboto.servicecatalog*), 18
search_provisioned_products_single_page () (*in module betterboto.servicecatalog*), 18
start_build_and_wait_for_completion () (*in module betterboto.codebuild*), 7