

---

**better-boto**

*Release 0.5.20*

**eamonn faherty**

**Apr 04, 2019**



CONTENTS:

|          |                                |          |
|----------|--------------------------------|----------|
| <b>1</b> | <b>Client</b>                  | <b>1</b> |
| 1.1      | What is this? . . . . .        | 1        |
| 1.2      | Classes . . . . .              | 1        |
| <b>2</b> | <b>CloudFormation helpers</b>  | <b>3</b> |
| 2.1      | What is this? . . . . .        | 3        |
| 2.2      | Methods . . . . .              | 3        |
| <b>3</b> | <b>Organizations helpers</b>   | <b>5</b> |
| 3.1      | What is this? . . . . .        | 5        |
| 3.2      | Methods . . . . .              | 5        |
| <b>4</b> | <b>Service Catalog helpers</b> | <b>7</b> |
| 4.1      | What is this? . . . . .        | 7        |
| 4.2      | Methods . . . . .              | 7        |
|          | <b>Python Module Index</b>     | <b>9</b> |



## CLIENT

### 1.1 What is this?

With the following clients you can use them as context managers and they provide extra functionality for you. Each client is documented below:

### 1.2 Classes



## **CLOUDFORMATION HELPERS**

### **2.1 What is this?**

The following methods are added to clients instantiated using Betterboto:

### **2.2 Methods**



## ORGANIZATIONS HELPERS

### 3.1 What is this?

The following methods are added to clients instantiated using Betterboto:

### 3.2 Methods

`betterboto.organizations.convert_path_to_ou(self, ou)`

This method accepts an ou and returns the path from the root account down to the ou

**Parameters**

- **self** – organizations client
- **ou** – the account

**Returns** the path from the root account down to the ou

`betterboto.organizations.list_children_nested(self, **kwargs)`

This method will return a list of all children (either ACCOUNT or ORGANIZATIONAL\_UNIT) for the given ParentId. It includes children, grandchildren lower levels of nesting.

**Parameters**

- **self** – organizations client
- **kwargs** – these are passed onto the list\_children method call

**Returns** list of children in the structure of [{ 'Id': "0123456789010"}, { 'Id': "1009876543210"}]

`betterboto.organizations.list_children_single_page(self, **kwargs)`

This will continue to call list\_children until there are no more pages left to retrieve. It will return the aggregated response in the same structure as list\_children does.

**Parameters**

- **self** – organizations client
- **kwargs** – these are passed onto the list\_children method call

**Returns** organizations\_client.list\_children.response



## SERVICE CATALOG HELPERS

### 4.1 What is this?

The following methods are added to clients instantiated using Betterboto:

### 4.2 Methods

`betterboto.servicecatalog.list_portfolios_single_page(self, **kwargs)`

This will continue to call `list_portfolios` until there are no more pages left to retrieve. It will return the aggregated response in the same structure as `list_portfolios` does.

**Parameters**

- **self** – servicecatalog client
- **kwargs** – these are passed onto the `list_portfolios` method call

**Returns** `servicecatalog_client.list_portfolios.response`

`betterboto.servicecatalog.list_provisioning_artifacts_single_page(self, **kwargs)`

This will continue to call `list_provisioning_artifacts` until there are no more pages left to retrieve. It will return the aggregated response in the same structure as `list_provisioning_artifacts` does.

**Parameters**

- **self** – servicecatalog client
- **kwargs** – these are passed onto the `list_provisioning_artifacts` method call

**Returns** `servicecatalog_client.list_provisioning_artifacts.response`

`betterboto.servicecatalog.search_products_as_admin_single_page(self, **kwargs)`

This will continue to call `search_products_as_admin` until there are no more pages left to retrieve. It will return the aggregated response in the same structure as `search_products_as_admin` does.

**Parameters**

- **self** – servicecatalog client
- **kwargs** – these are passed onto the `search_products_as_admin` method call

**Returns** `servicecatalog_client.search_products_as_admin.response`



## PYTHON MODULE INDEX

### b

`betterboto.organizations`, [5](#)  
`betterboto.servicecatalog`, [7](#)



## INDEX

### B

`betterboto.organizations` (*module*), 5  
`betterboto.servicecatalog` (*module*), 7

### C

`convert_path_to_ou()` (*in module betterboto.organizations*), 5

### L

`list_children_nested()` (*in module betterboto.organizations*), 5  
`list_children_single_page()` (*in module betterboto.organizations*), 5  
`list_portfolios_single_page()` (*in module betterboto.servicecatalog*), 7  
`list_provisioning_artifacts_single_page()` (*in module betterboto.servicecatalog*), 7

### S

`search_products_as_admin_single_page()` (*in module betterboto.servicecatalog*), 7